(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(10) International Publication Number WO 2011/101613 A1

(43) International Publication Date 25 August 2011 (25.08.2011)

(51) International Patent Classification:

G01N 1/04 (2006.01) H01J 37/305 (2006.01)

G01N 1/32 (2006.01)

(21) International Application Number:

PCT/GB2011/000169

(22) International Filing Date:

10 February 2011 (10.02,2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 1002645.8

17 February 2010 (17.02,2010)

GB

- (71) Applicant (for all designated States except US): LAN-CASTER UNIVERSITY BUSINESS ENTERPRISES LIMITED [GB/GB]; University House, Bailrigg, Lancaster LA1 4YW (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KOLOSOV, Oleg Victor [GB/GB]; Lancaster University Business Enterprises Limited, Research and Enterprise Services, Bowland Tower South, Lancaster University, Lancaster LAI AYT (GB). GRISHIN, Ilja [EE/GB]; Lancaster University Business Enterprises Limited, Research and Enterprise Services, Bowland Tower South, Lancaster University, Lancaster LAI AYT (GB).
- (74) Agent: INSTONE, Terry; Marks & Clerk LLP, Sussex House, 83 - 85 Mosley Street, Manchester M2 3LG (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4,17(iii))

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: METHOD AND APPARATUS FOR ION BEAM POLISHING



(57) Abstract: A method for forming a polished facet between an edge and a face of a sample, involves removing a first portion of the sample by directing an ion beam onto the edge adjacent the first portion along an ion beam axis to leave the polished facet. The ion beam axis lies on an ion beam plane oriented at a glancing incident angle, preferably from 1° to 30°, to a sample plane defined by and parallel to the first face. The ion beam is directed to flow from the edge towards the first face. Also disclosed is a sample preparation apparatus comprising a chamber adapted for evacuation with a sample holder adapted to hold a sample comprising a first face bounded by an edge, and an ion gun arranged to direct an ion beam along an ion beam axis towards the sample. The sample holder is configurable to position the sample relative to the ion beam such that a first portion of the sample is removable by the ion beam to leave a polished facet between the edge and the first face of said sample. The sample holder is configured to hold the sample whereby the ion beam axis lies on an ion beam plane oriented at an incident angle from 1° to 30° to a sample plane defined by and parallel to the first face of the sample.





A 5111/11/16/12 A